

ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type
b) fan efficiency [%]
c) VSD assumed in data
d) Measurement category
- e) Efficiency category
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
- g3) Δp [Pa]
h1) dual use fan
h2) reversible fan
h3) low noise fan
- i) DC voltage lower than 100 V
k) σBEP
l) fan speed [rpm]
m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CBD/B-1919-6M 1/10/HE	ErP Exclude. Pe < 125 W															
CBD/B-2525-4M 1/2/HE	forward curved centrifugal fan	38.8	VSD not necessary	C	Static	52.2	0.525	2089	351	No	No	No	No	0.00	1320	1.00
CBD/B-2525-4M 3/4/HE	forward curved centrifugal fan	39.3	VSD not necessary	C	Static	52.9	0.506	2137	335	No	No	No	No	0.00	1310	1.00
CBD/B-2525-6M 1/5/HE	forward curved centrifugal fan	40.0	VSD not necessary	D	Total	58.0	0.193	1925	144	No	No	No	No	0.00	850	1.00
CBD/B-2525-6M 1/3/HE	forward curved centrifugal fan	41.5	VSD not necessary	D	Total	58.8	0.224	2114	158	No	No	No	No	0.00	830	1.00
CBD/B-2828-4M 1/2/HE	forward curved centrifugal fan	43.3	VSD not necessary	C	Static	55.1	0.750	2490	469	No	No	No	No	0.00	1320	1.00
CBD/B-2828-4M 3/4/HE	forward curved centrifugal fan	43.4	VSD not necessary	C	Static	55.0	0.789	2544	485	No	No	No	No	0.00	1310	1.01
CBD/B-2828-6M 1/3/HE	forward curved centrifugal fan	37.7	VSD not necessary	C	Static	52.9	0.359	2265	215	No	No	No	No	0.00	830	1.00
CBD/B-3333-6M 3/4/HE	forward curved centrifugal fan	40.4	VSD not necessary	C	Static	52.4	0.716	3150	330	No	No	No	No	0.00	850	1.00
CBD/B-3939-6T 3/HE	forward curved centrifugal fan	44.7	VSD not necessary	C	Static	52.3	1.859	6604	453	No	No	No	No	0.00	890	1.01